



GREASE GB MoS₂

DESCRIPTION

GREASE GB MoS_2 is a heavy duty bearing greases containing molybdenum disulphide that has been designed for the effective lubrication and protection of ball, roller and plain bearings used in extreme pressure (EP) environments.



BENEFITS

- Contain extreme pressure additives
- High anti wear capacity
- Wide temperature range (-20°C to +130°C)
- Water resistant

PERFORMANCE LEVEL

NLGI 3

AVAILABLE IN 400gr

| TECHNICAL PROPERTIES | | |
|------------------------------------|------------|------------------|
| CHARACTERISTIC | TEST METOD | TYPICAL Value |
| Appearance | Visual | Grey |
| Thicker Type | | Li-complex |
| Worked penetration, at 25 °C, mm-1 | ASTM D217 | 250 |
| Drop Point, °C | ASTM D566 | 270 |
| Four Ball Test: | | |
| Weld Load, kg | ASTM D2596 | 450 |
| Mean Hertz Load, kg | ASTM D2596 | 90 |
| Corrosion Test | ASTM DI3N | la |

MSDS is available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. Take used oil to an authorised collection point. Do not discharge into drains, soil or water.