



# **GREASE LB**

#### DESCRIPTION

GREASE LB is a mineral lubricating grease of lithium base for different usage of lubrication (bearings-axes...). It consists of pure base oil, lithium soap and a set of chemical additives to give it the required specifications. The grease has smooth, homogeneous structure and light color. It is water-resistant, newly manufactured and has a high chemical and mechanical stability in lubrication.



#### **BENEFITS**

- Contain extreme pressure additives
- Wide temperature range (-20°C to +130°C)
- Water resistant

### PERFORMANCE LEVEL

**TECHNICAL PROPERTIES** 

NLGI 3

## **AVAILABLE IN** 400gr

	TESTINIONE I NOI ENTILE		
	CHARACTERISTIC	TEST METOD	TYPICAL Value
	Appearance	Visual	Grey
	Thicker Type		Li-complex
	Worked penetration, at 25 °C, mm-1	ASTM D217	250
	Drop Point, °C	ASTM D566	270
	Four Ball Test:		
	Weld Load, kg	ASTM D2596	450
	Mean Hertz Load, kg	ASTM D2596	90
	Corrosion Test	OEID MTZA	1a

MSDS is available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. Take used oil to an authorised collection point. Do not discharge into drains, soil or water.