

CHF Fluid

DESCRIPTION

CHF fluid is formulated with high-quality synthetic base stocks with an advanced additive combination. Performance hydraulic fluid for life-time application in modern vehicle aggregates like power steering, level control, shock absorber, hydro pneumatic suspension, stability and traction control, hydraulics for convertible tops, central lock systems. It has not been validated for use in braking systems, so should not be used in braking systems where an « LHM » fluid is required.

BENEFITS

- Quiet steering pump operation
- High resistance to oxidation
- High viscosity index
- Offers robust protection to seals and hoses

PERFORMANCE LEVEL

- Subaru ECVTF
- Matic-D
- Honda ZI
- MMC SP-III
- ZF TE-ML 14A
- MB 236.9
- Voith G607
- Allison C-4

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	Visual	Green
Density at 20°C, g/cm ³	ASTM D4052	0.862
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	6.7
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	33.5
Viscosity Index	ASTM D2270	162
Pour point, °C	ASTM D97	-50
Flash point, °C	ASTM D92	200
Copper Corrosion	ASTM D130	1a