

# SAE 50

## DESCRIPTION

SAE 50 is formulated with mineral base stocks and additives combined to meet the requirements of naturally aspired and turbocharged diesel and gasoline passenger cars and light trucks as well as farm equipment, especially where single grade oils are preferred.



## BENEFITS

- Provides excellent lubrication
- Good thermal- and oxidation stability
- Smoother, quitter drive

## PERFORMANCE LEVEL

- API SF/CF

## AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



## TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm <sup>3</sup>	ASTM D4052	0,880
Kinematic viscosity, 100 °C, mm <sup>2</sup> /s	ASTM D445	19
Kinematic viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	190
Viscosity Index	ASTM D2270	116
TBN, mg KOH/g	ASTM D2896	5
Pour point, °C	ASTM D97	-15
Flash point, °C	ASTM D92	230
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	1,1