

SAE 60

DESCRIPTION

SAE 60 is formulated with mineral base stocks and additives combined to meet the requirements of naturally aspired and turbocharged diesel and gasoline passenger cars and light trucks as well as farm equipment, especially where single grade oils are preferred.



BENEFITS

- Provides excellent lubrication
- Good thermal- and oxidation stability
- Smoother, quitter drive

PERFORMANCE LEVEL

- API SF/CF

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

| CHARACTERISTIC | TEST METHOD | TYPICAL VALUE |
|---|-------------|---------------|
| Appearance | Visual | Clear |
| Color | ASTM D1500 | 3 |
| Density at 20°C, g/cm ³ | ASTM D4052 | 0.880 |
| Kinematic viscosity, 100 °C, mm ² /s | ASTM D445 | 24 |
| Kinematic viscosity, 40 °C, mm ² /s | ASTM D445 | 250 |
| Viscosity Index | ASTM D2270 | 120 |
| TBN, mg KOH/g | ASTM D2896 | 5 |
| Pour point, °C | ASTM D97 | -15 |
| Flash point, °C | ASTM D92 | 230 |
| Copper Corrosion | ASTM D130 | 1a |
| Sulfated Ash, % m/m | ASTM D874 | 1,1 |