

MOTORCYCLE OIL

DESCRIPTION

2T oil specially designed for use in 2-stroke cycle motorcycles and motor scooters. It also is recommended for use in smaller air-cooled 2-stroke cycle engines found on portable lawn-care equipment, such as mowers, weed trimmers and leaf blowers. It may be used in either direct oil injection or premix engines.



BENEFITS

- Low-ash formulation
- Minimizes piston ring sticking
- Keeps engine parts clean
- Dyed for easy visibility

PERFORMANCE LEVEL

- API TC
- JASO FC

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm ³	ASTM D4052	0,875
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	9
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	70
Viscosity Index	ASTM D2270	102
TBN, mg KOH/g	ASTM D2896	0,9
Pour point, °C	ASTM D97	-30
Flash point, °C	ASTM D92	230
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	0,8